



Greenleaf  
Technologies

# AIR MIX

Drift control made easy.



- Excellent drift reduction. Less coarse than other air induction nozzles for better coverage at standard pressures.
- Optimal pressure range 20-60 psi, overall range 15-90 psi.
- Unique air cleaning system prevents air hole plugging.
- Excellent resistance to corrosive solutions. Two piece poly design can be cleaned without tools.
- Suggested spray height 16" to 24" (on 20" centers).
- Use with standard or Quick TeeJet flat spray caps or Greenleaf TipGuard™.

Order No.	Series No.	Tip Color	PSI	GPM 1 Nozzle	GPA — 20" Spacing				
					6 MPH	8 MPH	10 MPH	12 MPH	14 MPH
501928	AM11001	<b>Orange</b> (Use with 50 Mesh Strainer)	20	.07	3.5	2.6	2.1	1.7	1.5
			30	.09	4.3	3.2	2.6	2.1	1.8
			40	.10	4.9	3.7	3.0	2.5	2.1
			50	.11	5.5	4.1	3.3	2.8	2.4
			60	.12	6.1	4.5	3.6	3.0	2.6
501929	AM110015	<b>Green</b> (Use with 50 Mesh Strainer)	20	.11	5.2	3.9	3.1	2.6	2.2
			30	.13	6.4	4.8	3.9	3.2	2.8
			40	.15	7.4	5.6	4.5	3.7	3.2
			50	.17	8.3	6.2	5.0	4.1	3.6
			60	.18	9.1	6.8	5.5	4.5	3.9
501930	AM11002	<b>Yellow</b> (Use with 50 Mesh Strainer)	20	.14	7.0	5.2	4.2	3.5	3.0
			30	.17	8.6	6.4	5.1	4.3	3.7
			40	.20	9.9	7.4	5.9	4.9	4.2
			50	.22	11.1	8.3	6.6	5.5	4.7
			60	.24	12.1	9.1	7.3	6.1	5.2
501931	AM110025	<b>Turquoise</b> (Use with 50 Mesh Strainer)	20	.18	8.7	6.6	5.2	4.4	3.7
			30	.22	10.7	8.0	6.4	5.4	4.6
			40	.25	12.4	9.3	7.4	6.2	5.3
			50	.28	13.8	10.4	8.3	6.9	5.9
			60	.31	15.1	11.4	9.1	7.6	6.5
501932	AM11003	<b>Blue</b> (Use with 50 Mesh Strainer)	20	.21	10.5	7.9	6.3	5.2	4.5
			30	.26	12.9	9.6	7.7	6.4	5.5
			40	.30	14.8	11.1	8.9	7.4	6.4
			50	.34	16.6	12.4	10.0	8.3	7.1
			60	.37	18.2	13.6	10.9	9.1	7.8
501933	AM11004	<b>Red</b> (Use with 24 Mesh Strainer)	20	.28	14.0	10.5	8.4	7.0	6.0
			30	.35	17.1	12.9	10.3	8.6	7.3
			40	.40	19.8	14.8	11.9	9.9	8.5
			50	.45	22.1	16.6	13.3	11.1	9.5
			60	.49	24.2	18.2	14.5	12.1	10.4
501934	AM11005	<b>Brown</b> (Use with 24 Mesh Strainer)	20	.35	17.5	13.1	10.5	8.8	7.5
			30	.43	21.4	16.1	12.9	10.7	9.2
			40	.50	24.8	18.6	14.9	12.4	10.6
			50	.56	27.7	20.8	16.6	13.8	11.9
			60	.61	30.3	22.7	18.2	15.2	13.0
501935	AM11006	<b>Gray</b> (Use with 24 Mesh Strainer)	20	.42	21.0	15.8	12.6	10.5	9.0
			30	.52	25.7	19.3	15.4	12.9	11.0
			40	.60	29.7	22.3	17.8	14.9	12.7
			50	.67	33.2	24.9	19.9	16.6	14.2
			60	.74	36.4	27.3	21.8	18.2	15.6