

TeeJet®



Stainless Steel

150° Double Outlet Flat Spray Tips
for post-directed application with hose drops.

Order No.	TeeJet No.	PSI	GPM 1 Nozzle	GPA — 30" Spacing			
				6 MPH	8 MPH	10 MPH	12 MPH
501680	TQ15003SS (Use with 100 Mesh Strainer)	20	.21	7.0	5.3	4.2	3.5
		30	.26	8.6	6.4	5.1	4.0
		40	.30	9.9	7.4	5.9	4.3
		50	.34	11.1	8.3	6.6	5.5
		60	.37	12.1	9.1	7.3	6.1
501681	TQ15004SS (Use with 50 Mesh Strainer)	20	.28	9.3	7.0	5.6	4.7
		30	.35	11.4	8.6	6.9	5.7
		40	.40	13.2	9.9	7.9	6.6
		50	.45	14.8	11.1	8.9	7.4
		60	.49	16.2	12.1	9.7	8.1

Order No.	TeeJet No.	PSI	GPM 1 Nozzle	GPA — 30" Spacing			
				6 MPH	8 MPH	10 MPH	12 MPH
501682	TQ15005SS (Use with 50 Mesh Strainer)	20	.35	11.7	8.8	7.0	5.8
		30	.43	14.2	10.6	8.5	7.1
		40	.50	16.5	12.4	9.9	8.3
		50	.56	18.5	13.8	11.1	9.2
		60	.61	20.0	15.2	12.1	10.1
501683	TQ15006SS (Use with 50 Mesh Strainer)	20	.42	14.0	10.5	8.4	7.0
		30	.52	17.2	12.9	10.3	8.6
		40	.60	19.8	14.9	11.9	9.9
		50	.67	22.0	16.6	13.3	11.1
		60	.74	24.0	18.2	14.6	12.1
501684	TQ15008SS (Use with 50 Mesh Strainer)	20	.57	18.7	14.0	11.2	9.3
		30	.69	23.0	17.2	13.7	11.4
		40	.80	26.0	19.8	15.8	13.2
		50	.89	30.0	22.0	17.7	14.8
		60	.98	32.0	24.0	19.4	16.2
501685	TQ15009SS (Use with 50 Mesh Strainer)	20	.64	21.0	15.8	12.6	10.5
		30	.78	26.0	19.3	15.4	12.9
		40	.90	30.0	22.0	17.8	14.9
		50	1.00	33.0	25.0	19.9	16.6
		60	1.10	36.0	27.0	22.0	18.2