


# Turbo TeeJet® Induction

110° Flat Spray Tips



Polymer with  
VisiFlo® color-coding

Excellent for:

**Pre-emerge soil applied herbicides.**  
**Post-emerge systemic herbicides.**

- Rated excellent for drift management.
- Tapered edge wide angle flat spray pattern for uniform coverage in broadcast spraying.
- Large, round passages minimize clogging.
- All polymer construction with removable pre-orifice.
- Operating pressure range 15-100 psi.
- Automatic alignment when used with Shoup 501848 or TeeJet 25598-NYR caps.
- Due to pre-orifice design this tip is not compatible with check valve tip strainers (Shoup 501708, 501709 or TeeJet 4193A).

\* UC = Ultra Coarse; XC = Extra Coarse

Order No.	Series No.	Tip Color	PSI	* Drop Size	GPM 1 Nozzle	GPA — 20" Spacing			
						6 MPH	8 MPH	10 MPH	12 MPH
501920	TTI110015VP	<b>Green</b> (Use with 100 Mesh Strainer)	20	UC	.11	5.4	4.1	3.3	2.7
			30	UC	.13	6.4	4.8	3.9	3.2
			40	UC	.15	7.4	5.6	4.5	3.7
			50	UC	.17	8.4	6.3	5.0	4.2
			60	XC	.18	8.9	6.7	5.3	4.5
			70	XC	.20	9.9	7.4	5.9	5.0
501921	TTI11002VP	<b>Yellow</b> (Use with 50 Mesh Strainer)	20	UC	.14	6.9	5.2	4.2	3.5
			30	UC	.17	8.4	6.3	5.0	4.2
			40	UC	.20	9.9	7.4	5.9	5.0
			50	UC	.22	10.9	8.2	6.5	5.4
			60	UC	.24	11.9	8.9	7.1	5.9
			70	XC	.26	12.9	9.7	7.7	6.4
501922	TTI110025VP	<b>Purple</b> (Use with 50 Mesh Strainer)	20	UC	.18	8.9	6.7	5.3	4.5
			30	UC	.22	10.9	8.2	6.5	5.4
			40	UC	.25	12.4	9.3	7.4	6.2
			50	UC	.28	13.9	10.4	8.3	6.9
			60	UC	.31	15.3	11.5	9.2	7.7
			70	XC	.33	16.3	12.3	9.8	8.2
501923	TTI11003VP	<b>Blue</b> (Use with 50 Mesh Strainer)	20	UC	.21	10.4	7.8	6.2	5.2
			30	UC	.26	12.9	9.7	7.7	6.4
			40	UC	.30	14.9	11.1	8.9	7.4
			50	UC	.34	16.8	12.6	10.1	8.4
			60	UC	.37	18.3	13.7	11.0	9.2
			70	XC	.40	19.8	14.9	11.9	9.9
501924	TTI11004VP	<b>Red</b> (Use with 50 Mesh Strainer)	20	UC	.28	13.9	10.4	8.3	6.9
			30	UC	.35	17.3	13.0	10.4	8.7
			40	UC	.40	19.8	14.9	11.9	9.9
			50	UC	.45	22.0	16.7	13.4	11.1
			60	UC	.49	24.0	18.2	14.6	12.1
			70	XC	.53	26.0	19.7	15.7	13.1
501925	TTI11005VP	<b>Brown</b> (Use with 50 Mesh Strainer)	20	UC	.35	17.3	13.0	10.4	8.7
			30	UC	.43	21.0	16.0	12.8	10.6
			40	UC	.50	25.0	18.6	14.9	12.4
			50	UC	.56	28.0	21.0	16.6	13.9
			60	UC	.61	30.0	23.0	18.1	15.1
			70	XC	.66	33.0	25.0	19.6	16.3
501926	TTI11006VP	<b>Gray</b> (Use with 50 Mesh Strainer)	20	UC	.42	21.0	15.6	12.5	10.4
			30	UC	.52	26.0	19.3	15.4	12.9
			40	UC	.60	30.0	22.0	17.8	14.9
			50	UC	.67	33.0	25.0	19.9	16.6
			60	UC	.73	36.0	27.0	22.0	18.1
			70	XC	.79	39.0	29.0	23.0	19.6
80	XC	.85	42.0	32.0	25.0	21.0			