


Excellent: Pre-Emerge Surface Applied Herbicides - At medium pressures (20-30 psi) produces medium size droplets for good surface coverage in applications such as minimum tillage.

Excellent: Post-Emerge Systemic Herbicides- At lower pressures (15-20 psi) helps to control drift.

Excellent: Post-Emerge Contact Herbicides - At higher pressures (30-60 psi) produces smaller droplets for better coverage.

Excellent: Pre-Plant Incorporated Herbicides - At lower pressures (15-20 psi) produces larger spray droplets and reduces drift.

XR TeeJet®




**EXTENDED RANGE
FLAT SPRAY TIPS**

At 15 psi pressure At 60 psi pressure

**Stainless Steel with
VisiFlo® color-coding**

SUGGESTED MINIMUM SPRAY HEIGHT

SPRAY ANGLE	SPRAY HEIGHT 20" SPACING
80°	17" - 19"
110°	15" - 18"



Adjust spray height in the field to overlap approximately 30% of each edge of pattern.

Order No.	TIP NUMBER		TIP COLOR	Liquid Pressure PSI	Capacity 1 Nozzle GPM	Capacity 1 Nozzle oz./min.	Gallons Per Acre — 20" Spacing							
	80° Series	110° Series					4 MPH	5 MPH	6 MPH	8 MPH	10 MPH	12 MPH	15 MPH	20 MPH
501720	XR8001VS	—	Orange (Use with 100 Mesh Strainer)	15	.06	8	4.5	3.6	3.0	2.3	1.8	1.5	1.2	0.9
501721	—	XR11001VS		20	.07	9	5.3	4.2	3.5	2.6	2.1	1.8	1.4	1.1
				30	.09	11	6.5	5.2	4.3	3.2	2.6	2.2	1.7	1.3
				40	.10	13	7.4	5.9	5.0	3.7	3.0	2.5	2.0	1.5
			60	.12	15	8.9	7.1	5.9	4.5	3.6	3.0	2.4	1.8	
501722	XR80015VS	—	Green (Use with 100 Mesh Strainer)	15	.09	12	6.8	5.5	4.6	3.4	2.7	2.3	1.8	1.4
501723	—	XR110015VS		20	.11	14	8.2	6.9	5.4	4.1	3.3	2.7	2.2	1.6
				30	.13	17	9.7	7.7	6.4	4.8	3.9	3.2	2.6	1.9
				40	.15	19	11.1	8.9	7.4	5.6	4.5	3.7	3.0	2.2
			60	.18	23	13.4	10.7	8.9	6.7	5.3	4.5	3.6	2.7	
501724	XR8002VS	—	Yellow (Use with 50 Mesh Strainer)	15	.12	15	8.9	7.1	5.9	4.5	3.6	3.0	2.4	1.8
501725	—	XR11002VS		20	.14	18	10.4	8.3	6.9	5.2	4.2	3.5	2.8	2.1
				30	.17	22	12.6	10.1	8.4	6.3	5.0	4.2	3.4	2.5
				40	.20	26	14.9	11.9	9.9	7.4	5.9	5.0	4.0	3.0
			60	.24	31	17.8	14.3	11.9	8.9	7.1	5.9	4.8	3.6	
501726	XR8003VS	—	Blue (Use with 50 Mesh Strainer)	15	.18	23	13.4	10.7	8.9	6.7	5.3	4.5	3.6	2.7
501727	—	XR11003VS		20	.21	27	15.6	12.5	10.4	7.8	6.2	5.2	4.2	3.1
				30	.26	33	19.3	15.4	12.9	9.7	7.7	6.4	5.1	3.9
				40	.30	38	22.0	17.8	14.9	11.1	8.9	7.4	5.9	4.5
			60	.37	47	27.0	22.0	18.3	13.7	11.0	9.2	7.3	5.5	
501728	XR8004VS	—	Red (Use with 50 Mesh Strainer)	15	.24	31	17.8	14.3	11.9	8.9	7.1	5.9	4.8	3.6
501729	—	XR11004VS		20	.28	36	21.0	16.6	13.9	10.4	8.3	6.9	5.5	4.2
				30	.35	45	26.0	21.0	17.3	13.0	10.4	8.7	6.9	5.2
				40	.40	51	30.0	24.0	19.8	14.9	11.9	9.9	7.9	5.9
			60	.49	63	36.0	29.0	24.0	18.2	14.6	12.1	9.7	7.3	
501730	XR8005VS	—	Brown (Use with 50 Mesh Strainer)	15	.31	40	23.0	18.4	15.3	11.5	9.2	7.7	6.1	4.6
501731	—	XR11005VS		20	.35	45	26.0	21.0	17.3	13.0	10.4	8.7	6.9	5.2
				30	.43	55	32.0	26.0	21.0	16.0	12.8	10.6	8.5	6.4
				40	.50	64	37.0	30.0	25.0	18.6	14.9	12.4	9.9	7.4
			60	.61	78	45.0	36.0	30.0	23.0	18.1	15.1	12.1	9.1	
501732	XR8006VS	—	Gray (Use with 50 Mesh Strainer)	15	.37	47	27.0	22.0	18.3	13.7	11.0	9.2	7.3	5.5
501733	—	XR11006VS		20	.42	54	31.0	25.0	21.0	15.6	12.5	10.4	8.3	6.2
				30	.52	67	39.0	31.0	26.0	19.3	15.4	12.9	10.3	7.7
				40	.60	77	45.0	36.0	30.0	22.0	17.8	14.9	11.9	8.9
			60	.73	93	54.0	43.0	36.0	27.0	22.0	18.1	14.5	10.8	
501734	XR8008VS	—	White	15	.49	63	36.0	29.0	24.0	18.2	14.6	12.1	9.7	7.3
501735	—	XR11008VS		20	.57	73	42.0	34.0	28.0	21.0	16.9	14.1	11.3	8.5
				30	.69	88	51.0	41.0	34.0	26.0	20.0	17.1	13.7	10.2
				40	.80	102	59.0	48.0	40.0	30.0	24.0	19.8	15.8	11.9
			60	.98	125	73.0	58.0	49.0	36.0	29.0	24.0	19.4	14.6	
501736	XR8010SS	—	Use with 501856 cap	15	.61	78	45.0	36.0	30.0	23.0	18.1	15.1	12.1	9.1
501737	—	XR11010SS		20	.71	91	53.0	42.0	35.0	26.0	21.0	17.6	14.1	10.5
				30	.87	111	65.0	52.0	43.0	32.0	26.0	22.0	17.2	12.9
				40	1.00	128	74.0	59.0	50.0	37.0	30.0	25.0	19.8	14.9
			60	1.22	156	91.0	72.0	60.0	45.0	36.0	30.0	24.0	18.1	